

Deposited candy Line

Model: YGD/150/300/450/600



Main Features

- PLC controlled fully automatic Hard Boiled Candy Cooking & Depositing line.
- Available in two models, servo controlled or mechanical transmission system.
- A simple & user friendly LED touch screen Panel for operating and controlling the line.
- An excellent choice for producing clear transparent fruit flavored candies.
- Optional online milk injection unit for producing white milk candies.
- Both milk and caramel based candies can be handled without the risk of burning, thereby minimizing cleaning cycles.
- Online flavored & acid dosing and mixing units.
- Can produce solid, striped and center filled candies.
- Requires minimum space & low utility loads.

Technical Parameter

Model No.	YGD 150	YGD 300	YGD 450	YGD 600
System	Servo Controlled (or) Mechanical Transmission			
Capacity/Hour	150 Kg	300 Kg	450 Kg	600 Kg
Weight of Candy	2.5 g to 10g			
Number of Strokes/Minute	35 to 55, Depending on Product Weight			
No of Candies per stroke	20	40	60	80
Moulds	Teflon Coated Aluminum Moulds with Teflon Ejector Pins (candy release)			
Power Required	18 Kw / 380 V	38 Kw / 380 V	40 Kw / 380 V	42 Kw / 380 V
Steam Required	200 Kg/Hour	400 Kg/Hour	600 Kg/Hour	800 Kg/Hour
Steam Pressure	e "0.6 Mpa			
Compact Air Required	0.5M/Min	0.6M/Min	0.6M/Min	0.6M/Min
Size of Line	15*1.2*2.3 (M)	17*1.8*2.6 (M)	17*2.2*2.6 (M)	17*2.5*2.6 (M)